

## MEDICAL CENTER OF THE AMERICAS

EL PASO, TEXAS




SMARTCODE - TITLE 21 APPLICATION
JUNE 2011 - REVISED AREA

### **TABLE OF CONTENTS**


| ABLE OF CONTENTS        |   |
|-------------------------|---|
| EXISTING SITE AERIAL    |   |
| SITE PLAN               |   |
| EXISTING ZONING         |   |
| COMMUNITY TYPE          | ( |
| Ransect zone allocation |   |
| CIVIC SPACES            |   |
| HOROUGHFARE NETWORK     | • |
| BLOCK PERIMETER         | ( |
| THOROUGHFARE ASSEMBLIES |   |
| DECIAL DECLIDEMENTS     |   |













#### C. Infill RCD (Regional Center Development)

1. An Infill RCD should be assigned to downtown areas that include significant office and retail uses as well as government and other civic institutions of regional importance. An Infill RCD shall be mapped as at least one complete long or linear pedestrian shed, which may be adjusted as a network pedestrian shed, oriented around an important mixed use 2. The edges of an Infill RCD should blend into adjacent neighborhoods without buffers.

#### D. Infill TOD (Transit-Oriented Development)

1. Any Infill TND or Infill RCD on an existing or projected rail or bus rapid transit (BRT) network may be redesignated in whole or in part as TOD and permitted the higher density represented by the effective parking allowance in Section MCA Planning Area =132 acres





#### 20.40.030 Transect Zones

A. Transect Zone Standards for Infill Regulating Plans should be calibrated by means of a survey of exemplary existing and intended conditions, as identified in a process of public consultation and subject to the approval of the City Council. Metrics shall be recorded on Table 14 and Table 15.

B. A Transect Zone shall include elements indicated by Chapters 21.30, 21.50 and 21.60.

#### 21.80.170 Table 14 Requirements for a RCD:

T6 = 40 - 60%

T5 = 10 - 30%

T40 = 50% max.

T4 = 10 - 30%

Recommended allocations. Not required for Chapter 20.40 Application.

## INFILL RCD TRANSECT ALLOCATIONS


# T6 T5 T4O T4 SD Civic Total 77.4 54.7 47.9 54.4 73.6 72.5 384.6\* 20.1% 14.2% 12.5% 14.1% 18.1% 18.9% 100% \*Net Site Area - all developable land within a site including Thor


\*Net Site Area - all developable land within a site including oughfares but excluding land allocated as T1.

#### MCA TRANSECT ALLOCATIONS

| T6    | T5  | T4   | SD    | Civic | Total  |
|-------|-----|------|-------|-------|--------|
| 44.5  | 1.0 | 0.8  | 73.6  | 2.3   | 130.7* |
| 34.0% | .8% | 0.6% | 56.3% | 1.8%  | 100%   |

\*Net Site Area - all developable land within a site including Thoroughfares but excluding land allocated as T1.





#### 21.40.040 Civic Zones

#### A. General

- **1.** Infill Plans should designate civic space zones (CS) and civic building zones (CB).
- **2.** A civic zone may be permitted if it does not occupy more than 20% of a pedestrian shed, otherwise it is subject to the creation of a special district. See Section 21.40.050.
- 3. Parking for civic zones shall be calculated per the stan-

dards of Chapter 20.14 and Appendix C of this code. On street parking available along the frontage lines that correspond to each lot shall be counted toward the parking requirement of the building on the lot. The required parking may also be provided within on-quarter mile of the site that it serves.

#### B. Civic Space Zones (CS)


**1.** Civic spaces shall be generally designed as described in Table 13, their type determined by the surrounding or adja-


cent Transect Zone in a process of public consultation subject to the approval of the City Council.

#### C. Civic Building Zones (CB)

- **1.** Civic buildings shall be permitted on civic zones reserved in the infill regulating plan.
- **2.** Civic buildings shall be subject to the requirements of Chapter 21.50.









**B.2.b.(3)** A thoroughfare network, existing or planned (Table 3A, Table 3B, Table 4A, Table 4B and Table 4C);

ing condition contraints. New connections are made where possible, however this RCD has the additional limitation of the railway.




THOROUGHFARE NETWORK




**21.10.040** Infill Regulating Plans shall consist of one or more maps showing the following:

**B.2.b.(3)** A thoroughfare network, existing or planned (Table 3A, Table 3B, Table 4A, Table 4B and Table 4C);




#### KEY




## THOROUGHFARE TYPES Boulevard:

| Avenue:             | A' |
|---------------------|----|
| Commercial Street:  | С  |
| Street:             | ST |
| Road:               | RI |
| Rear Alley:         | R/ |
| Rear Lane:          | RI |
| TRANSPORTATION TYPE |    |
| Bicycle Lane:       | BL |
| Bicycle Trail:      | ВТ |
| Bicycle Route:      | BF |
| Sharrow:            | SI |
| Path:               | P. |
| Transit Route:      | TR |
|                     |    |


| Thoroug         | hfare Type  |
|-----------------|-------------|
| Transect Zone A | Assignment  |
| Right-of-       | Way Width   |
| Paven           | nent Width  |
| 1               | Movement    |
| Des             | ign Speed   |
| Pedestrian Cro  | ossing Time |
| Tro             | affic Lanes |
| Par             | king Lanes  |
| С               | urb Radius  |
| Public Fron     | itage Type  |
| Wal             | kway Type   |
| Pl              | anter Type  |
|                 | Curb Type   |
| Landso          | саре Туре   |
| Transportatio   | n Provision |





None




| CS-50-22                   |  |
|----------------------------|--|
| Commercial Street          |  |
| T5, T6                     |  |
| 50 feet                    |  |
| 22 feet                    |  |
| Slow Movement              |  |
| 20 MPH                     |  |
| 6.2 seconds                |  |
| 1 lane                     |  |
| One side @ 8 feet marked   |  |
| 15 feet                    |  |
| Arcade, Gallery, Shopfront |  |
| 18/10 foot Sidewalk        |  |
| 4'x4' tree well            |  |
| Vertical                   |  |
| Trees at 30' o.c. Avg.     |  |
| TR, SH                     |  |









AV-75-44 or CS-70-36(+5)

AV-75-40\*

70'

44'

13' 16' 10'10'8' 13'

#### KEY


|                      | ST-57-20-SH |
|----------------------|-------------|
| Thoroughfare Type —  |             |
| Right of Way Width — |             |
| Pavement Width —     |             |
| Transportation ——    |             |

## THOROUGHFARE TYPES Boulevard:

| boolevara.          | U  |
|---------------------|----|
| Avenue:             | Α  |
| Commercial Street:  | С  |
| Street:             | ST |
| Road:               | RI |
| Rear Alley:         | R  |
| Rear Lane:          | RI |
| TRANSPORTATION TYPE |    |
| Bicycle Lane:       | Bl |
| Bicycle Trail:      | B  |
| Bicycle Route:      | В  |
| Sharrow:            | SI |
| Path:               | P  |
| Transit Route:      | TR |
|                     |    |

| Thoroughfare Typ        |
|-------------------------|
| Transect Zone Assignme  |
| Right-of-Way Wid        |
| Pavement Wid            |
| Moveme                  |
| Design Spee             |
| Pedestrian Crossing Tim |
| Traffic Lane            |
| Parking Lane            |
| Curb Radi               |
| Public Frontage Typ     |
| Walkway Typ             |
| Planter Typ             |
| Curb Typ                |
| Landscape Typ           |

Transportation Provision





#### 20.40.070 Special Requirements

A. An infill community plan may designate any of the following special requirements:

1. A differentiation of the thoroughfares as A-Grid and B-Grid.

3. Designations for mandatory and/or recommended gallery frontage, requiring or advising that a building provide a permanent cover over the sidewalk, either cantilevered or supported by columns.

